

XTL™ Labels

Flexible Cable Wrap

- For labeling wires, cables and rounded surfaces
- Constructed of durable, flexible nylon material designed to conform and stick
- Tear-proof material resists damage when pulled through tight spaces or conduits
- Easy-to-peel split back design makes applying labels quick and easy
- Durable thermal transfer printing technology – label text won't smear or fade
- RoHS compliant



Quick Specs

Label Widths	12, 19, 24 mm
Tape Platform	XTL
Printer Compatibility	XTL 300, XTL 500
Label Length	5.5 m
Printing System	Thermal Transfer
Temperature Rating	-40°C to 60°C
UL Recognized	Component to UL 969
Country of Origin	Belgium
Material	Flex Nylon

Item Number	Width (in)	Color		Length (mm)	Width (mm)	Height (mm)	Weight (kg)	QTY	EAN
1868806	12 mm	A	Unit	72	35	120	0.05	1	071701001856
			Shelf	215	76	126	0.37	6	30071701001857
			Case	400	230	145	2.17	30	50071701001851
			Pallet	1200	800	1165	162.02	63	-
1868807	19 mm	A	Unit	72	35	120	0.07	1	071701001863
			Shelf	215	76	126	0.46	6	30071701001864
			Case	400	230	145	2.58	30	50071701001868
			Pallet	1200	800	1165	187.54	63	-
1868808	24 mm	A	Unit	72	35	120	0.08	1	071701001870
			Shelf	215	76	126	0.52	6	30071701001871
			Case	400	230	145	2.89	30	50071701001875
			Pallet	1200	800	1165	207.38	63	-

A NewellRubbermaid Company™

SCHAWK!

RMZ Millennia Business Park
Campus - 2, 5th Floor
No. 143, Dr.M. G. R. Road
Kandanchavadi | Chennai 600 098 India
T +91 44 4213 7777 | www.schawk.com



Use the PANTONE MATCHING SYSTEM for accurate color reproduction

VERSION	JOB DESCRIPTION : NRM_EU_Writing_Dymo_1363856.07_XTL_SS_Product Fact Book_2015 FILE NAME : 1363856_WDY_SS_RD_Flexible_Cable_Wrap_EMEA_v3.indd	BRAND : DYMO
3 Date: 08-07-2015 Operator : BR	SCHAWK JOB # : 352185I NRM JOB # : 1363856 COMPONENT # : N/A	CATEGORY OF WORK : COLLATERALS NO. OF PAGES# : 1 PAGE SIZE : A4

Note :